

WHAT IS CLAIMED IS:

1. A method for authenticated access to multicast traffic, comprising:

receiving a request for a user to join a multicast channel;

authenticating access privileges of the user to the multicast channel; and

disallowing the request in response to at least an unsuccessful authentication.

2. The method of Claim 1, authenticating access privileges of the user comprising:

determining whether the user has access privileges to the multicast channel based on previously provisioned information for the user; and

unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not having access privileges to the multicast channel.

3. The method of Claim 1, wherein the multicast channel comprises an Internet protocol (IP) multicast channel and the request comprises an Internet group management protocol (IGMP) join request.

4. The method of Claim 1, further comprising allowing the request in response to at least successful authentication.

5. The method of Claim 1, wherein the multicast channel comprises at least one of video, audio, data and combinational content.

6. The method of Claim 1, further comprising:
prior to receiving the request, provisioning the
user's access privileges in an authentication,
authorization, and accounting (AAA) server; and
5 accessing the AAA server to authenticate access
privileges of the user to the multicast channel.

7. The method of Claim 6, wherein the AAA server
comprises a remote authentication dial-in user service
10 (RADIUS) server.

8. The method of Claim 1, wherein the multicast
channel comprises an Internet protocol (IP) multicast
channel and the request includes an IP address of the
15 user device, further comprising determining the user
based on the IP address of the device.

9. The method of Claim 1, authenticating access
privileges of the user comprising:
20 determining whether the multicast channel comprises
a public multicast channel; and
successfully authenticating access privileges of the
user to the multicast channel in response to at least the
multicast channel comprising the public multicast
25 channel.

10. The method of Claim 1, authenticating access privileges of the user comprising:

determining whether the user is logged in to a service provider providing the multicast channel; and

5 unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not logged in to the service provider.

11. The method of Claim 1, authenticating access privileges of the user comprising:

determining whether the user is logged in to a service including the multicast channel; and

15 unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not logged in to the service including the multicast channel.

12. The method of Claim 1, authenticating access privileges of the user comprising:

20 determining whether the user is logged in to a service provider providing a service including the multicast channel;

determining whether the user is logged in to the service including the multicast channel; and

25 successfully authenticating access privileges of the user to the multicast channel in response to at least the user logged in to the service provider and the service.

13. The method of Claim 1, wherein the request is a subscriber join request.

14. The method of Claim 1, authenticating access privileges of the user comprising:

determining whether the multicast channel is a controlled access multicast channel; and

5 authenticating access privileges of the user to the multicast channel in response to at least the multicast channel comprising the controlled access multicast channel.

10 15. The method of Claim 1, further comprising:

determining if authentication is enabled at an access router receiving the request;

authenticating access privileges of the user to the multicast channel in response to at least determining

15 that authentication is enabled; and

allowing the request in response to at least determining authentication is not enabled.

16. A system for authenticated access to multicast traffic, comprising:

means for receiving a request for a user to join a multicast channel;

5 means for authenticating access privileges of the user to the multicast channel; and

means for disallowing the request in response to at least an unsuccessful authentication.

10 17. A system of Claim 16, the means for authenticating access privileges of the user comprising:

means for determining whether the user has access privileges to the multicast channel based on previously provisioned information for the user; and

15 means for unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not having access privileges to the multicast channel.

20 18. A system of Claim 16, wherein the multicast channel comprises an Internet protocol (IP) multicast channel and the request comprises an Internet group management protocol (IGMP) join request.

25 19. A system of Claim 16, further comprising means for allowing the request in response to at least successful authentication.

30 20. A system of Claim 16, wherein the multicast channel comprises at least one of video, audio, data and combinational content.

21. A system of Claim 16, further comprising:

means for, prior to receiving the request,
provisioning the user's access privileges in an
authentication, authorization, and accounting (AAA)
server; and

means for accessing the AAA server to authenticate
access privileges of the user to the multicast channel.

22. A system of Claim 21, wherein the AAA server
comprises a remote authentication dial-in user service
(RADIUS) server.

23. A system of Claim 16, wherein the multicast
channel comprises an Internet protocol (IP) multicast
channel and the request includes an IP address of the
user device, further comprising means for determining the
user based on the IP address of the device.

24. A system of Claim 16, the means for
authenticating access privileges of the user comprising:

means for determining whether the multicast channel
comprises a public multicast channel; and

means for successfully authenticating access
privileges of the user to the multicast channel in
response to at least the multicast channel comprising the
public multicast channel.

25. A system of Claim 16, the means for authenticating access privileges of the user comprising:

means for determining whether the user is logged in to a service provider providing the multicast channel;
5 and

means for unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not logged in to the service provider.

10 26. A system of Claim 16, the means for authenticating access privileges of the user comprising:

means for determining whether the user is logged in to a service including the multicast channel; and

15 means for unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not logged in to the service including the multicast channel.

20 27. A system of Claim 16, the means for authenticating access privileges of the user comprising:

means for determining whether the user is logged in to a service provider providing a service including the multicast channel;

25 means for determining whether the user is logged in to the service including the multicast channel; and

means for successfully authenticating access privileges of the user to the multicast channel in response to at least the user logged in to the service provider and the service.
30

28. A system of Claim 16, wherein the request is a subscriber join request.

29. A system of Claim 16, the means for
5 authenticating access privileges of the user comprising:
means for determining whether the multicast channel
is a controlled access multicast channel; and
means for authenticating access privileges of the
user to the multicast channel in response to at least the
10 multicast channel comprising the controlled access
multicast channel.

30. A system of Claim 16, further comprising:
means for determining if authentication is enabled
15 at an access router receiving the request;
means for authenticating access privileges of the
user to the multicast channel in response to at least
determining that authentication is enabled; and
means for allowing the request in response to at
20 least determining authentication is not enabled.

31. A system for authenticated access to multicast traffic, comprising:

logic encoded in media; and

5 the logic operable to receive a request for a user to join a multicast channel, to authenticate access privileges of the user to the multicast channel and to disallow the request in response to at least an unsuccessful authentication.

10 32. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

determining whether the user has access privileges to the multicast channel based on previously provisioned information for the user; and

15 unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not having access privileges to the multicast channel.

20 33. The system of Claim 31, wherein the multicast channel comprises an Internet protocol (IP) multicast channel and the request comprises an Internet group management protocol (IGMP) join request.

25 34. The system of Claim 31, the logic further operable to allow the request in response to at least successful authentication.

30 35. The system of Claim 31, wherein the multicast channel comprises at least one of video, audio, data and combinational content.

36. The system of Claim 31, the logic further operable to:

prior to receiving the request, provision the user's access privileges in an authentication, authorization, and accounting (AAA) server; and

access the AAA server to authenticate access privileges of the user to the multicast channel.

37. The system of Claim 36, wherein the AAA server comprises a remote authentication dial-in user service (RADIUS) server.

38. The system of Claim 31, wherein the multicast channel comprises an Internet protocol (IP) multicast channel and the request includes an IP address of the user device, the logic further operable to determine the user based on the IP address of the device.

39. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

determining whether the multicast channel comprises a public multicast channel; and

successfully authenticating access privileges of the user to the multicast channel in response to at least the multicast channel comprising the public multicast channel.

40. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

determining whether the user is logged in to a service provider providing the multicast channel; and

5 unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least the user not logged in to the service provider.

41. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

10 determining whether the user is logged in to a service including the multicast channel; and

 unsuccessfully authenticating access privileges of the user to the multicast channel in response to at least
15 the user not logged in to the service including the multicast channel.

42. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

20 determining whether the user is logged in to a service provider providing a service including the multicast channel;

 determining whether the user is logged in to the service including the multicast channel; and

25 successfully authenticating access privileges of the user to the multicast channel in response to at least the user logged in to the service provider and the service.

43. The system of Claim 31, wherein the request is
30 a subscriber join request.

44. The system of Claim 31, the logic operable to authenticate access privileges of the user by:

determining whether the multicast channel is a controlled access multicast channel; and

5 authenticating access privileges of the user to the multicast channel in response to at least the multicast channel comprising the controlled access multicast channel.

10 45. The system of Claim 31, the logic further operable to:

determine if authentication is enabled at an access router receiving the request;

15 authenticate access privileges of the user to the multicast channel in response to at least determining that authentication is enabled; and

allow the request in response to at least determining authentication is not enabled.

46. A method for providing premium content services over a network using Internet protocol (IP) multicast channels, comprising:

5 provisioning user access privileges to an IP multicast channel providing premium content, the premium content including at least one of video, audio and data;

10 authenticating access privileges of a user to the IP multicast channel upon receiving a request for the user to join the IP multicast channel to receive the premium video content; and

disallowing the request in response to unsuccessful authentication.

47. A method for authenticated access to multicast traffic, comprising:

receiving a request for a user to join an Internet protocol (IP) multicast channel;

5 authenticating access privileges of the user to the IP multicast channel by at least one of:

determining whether the IP multicast channel is a public multicast channel;

10 determining whether the user is logged in to a service provider providing a service including the IP multicast channel;

determining whether the user is logged in to the service including the IP multicast channel;

15 successfully authenticating access privileges of the user to the IP multicast channel in response to at least one of determining the multicast channel is a public multicast channel and determining the user is logged in to the service provider and the service;

20 unsuccessfully authenticating access privileges of the user to the IP multicast channel in response to at least one of determining the user is not logged in to the service provider and determining the user is not logged in to the service;

25 terminating the request in response to at least an unsuccessful authentication; and

processing the request in response to at least a successful authentication.